

Model: GLOBE BRICK LHASA**Codes:** 100001584 - L153201511**Group:** G-270**Format:** 3 15/16" X 15 3/4" approx.**Thickness:** 25/32 " approx.

RECOMMENDATIONS

Recommended adhesive	100031189 SUPER-ONE N GRIS	
Recommended joint	No admite rejuntado	
Recommended joint (wet area)	No admite rejuntado	
Recommended adhesive (wet area)	No Procede	

ADDITIONAL NOTES

The thickness indicated in the parts code corresponds to the nominal size. However, due to the fact that it is an artisan extraction and manufacture, parts may eventually be served with thicknesses close to the nominal size depending on availability.

LABORATORY TESTS

Bulk density	2320 Kg/m3	UNE EN 1936:2007*
Water absorption at atmospheric pressure	0.21%	UNE-EN 13755:2002*
Flammability	A1f I/A1	UNE-EN 13501-1:2007+A1:2010*
Frost resistance	23.1 MPa	UNE-EN 12371:2011*
Resistance to thermal shock	-0.03%/7.9%	UNE -EN 16140:2011*
Resistance to abrasion (except g.7-8)	19.5 mm	UNE-EN 14157:2005*
Flexural strength	22.9 MPa	UNE-EN 12372:2007*

FEATURES

-  There are slight color changes between pieces.
-  Material from an Asian country.
-  Material suitable for use on indoor walls.
-  Gloss-free
-  Material suitable for use on outdoor walls.
-  Material that stands out for having an asymmetrical surface.

PACKING

Boxes	4,31 SQF/CS	
Pallets	180,83 SQF/PAL	
Units	0,43 SQF/ST	
Sale unit	M2	
Base unit	PIECES	
Net weight	115,74 LB/M2	
Gross weight	119,82 LB/M2	

