

Model: GLOBE BRICK INDIRA**Codes:** 100044752 - L153201581**Group:** G-255**Format:** 3 15/16" X 15 3/4" approx.**Thickness:** 25/32 " approx.

RECOMMENDATIONS

| | | |
|---------------------------------|----------------------------|--|
| Recommended adhesive | 100031189 SUPER-ONE N GRIS | |
| Recommended joint | No admite rejuntado | |
| Recommended joint (wet area) | No admite rejuntado | |
| Recommended adhesive (wet area) | No Procede | |

ADDITIONAL NOTES

The thickness indicated in the parts code corresponds to the nominal size. However, due to the fact that it is an artisan extraction and manufacture, parts may eventually be served with thicknesses close to the nominal size depending on availability.

LABORATORY TESTS

| | | |
|--|------------------------|------------------------------|
| Bulk density | 2320 Kg/m ³ | UNE EN 1936:2007* |
| Water absorption at atmospheric pressure | 0.21% | UNE-EN 13755:2002* |
| Flammability | A1f I/A1 | UNE-EN 13501-1:2007+A1:2010* |
| Frost resistance | 23.1 MPa | UNE-EN 12371:2011* |
| Resistance to thermal shock | -0.03%/7.9% | UNE -EN 16140:2011* |
| Resistance to abrasion (except g.7-8) | 19.5 mm | UNE-EN 14157:2005* |
| Flexural strength | 22.9 MPa | UNE-EN 12372:2007* |

FEATURES

-  There are consistent color changes between pieces.
-  Material from an Asian country.
-  Material suitable for use on indoor walls.
-  Gloss-free
-  Material suitable for use on outdoor walls.
-  Material that stands out for having an asymmetrical surface.

PACKING

| | | |
|--------------|-------------|--|
| Boxes | 5,17 SQF/CS | |
| Pallets | 217 SQF/PAL | |
| Units | 0,43 SQF/ST | |
| Sale unit | M2 | |
| Base unit | PIECES | |
| Net weight | 70,55 LB/M2 | |
| Gross weight | 73,03 LB/M2 | |