

Model: CHENNAI WHITE FLAMED HOME**Codes:** 100086252 - L107000151**Group:** G-246**Format:** 15 3/4" X 31 1/2" approx.**Thickness:** 9/16 " approx.

RECOMMENDATIONS

Recommended adhesive	100031189 SUPER-ONE N GRIS	
Recommended joint	100236834 COLORSTUK RAPID GRIS N	
Recommended joint (wet area)	100236834 COLORSTUK RAPID GRIS N	100086920 FILA FOB EXTREME
Recommended adhesive (wet area)	100031189 SUPER-ONE N GRIS	

TOLERANCES

Indoor tolerance	1 mm (ancho), 1.5 mm (largo), $\pm 10\%$ (espesor)	EN 1469:2004 EN 12058:2004*
Outdoor tolerance	± 4 mm (ancho), ± 4 mm (largo), $\pm 3\%$ (espesor)	UNE-EN 1341:2002*

LABORATORY TESTS

Bulk density	2870 Kg/m ³	UNE EN 1936:2007*
Water absorption at atmospheric pressure	0.58%	UNE-EN 13755:2002*
Slip resistance	Húmedo: Clase 3/Seco: Clase 3	UNE 41901 / UNE 41902*
Flammability	A1f I/A1	UNE-EN 13501-1:2007+A1:2010*
Frost resistance	10.6 MPa	UNE-EN 12371:2011*
Resistance to thermal shock	0.01%/4.9%	UNE -EN 16140:2011*
Resistance to abrasion (except g.7-8)	17.5 mm	UNE-EN 14157:2005*
Slip resistance (dcof)	0.77	ANSI A137.1*
Flexural strength	12.8 MPa	UNE-EN 12372:2007*

FEATURES

-  Protection that reduces the appearance of the most common domestic bacteria.
-  Material from an Asian country.
-  Gloss-free
-  Material suitable for use on outdoor walls.
-  Material suitable for use on indoor floors.
-  Material suitable for use on shower floors.
-  There are consistent color changes between pieces.
-  Material suitable for use on indoor walls.
-  Material suitable for use on pool surroundings.
-  Material suitable for use on shower walls.
-  Material suitable for use on outdoor floors.

PACKING

Boxes	3,44 SQF/CS	
Pallets	268,67 SQF/PAL	
Units	3,44 SQF/ST	
Sale unit	M2	
Base unit	PIECES	
Net weight	97,39 LB/M2	
Gross weight	99,33 LB/M2	

