

Model: AIRSLATE FOREST

Codes: 100161514 - L106200901


Group: G-238

Format: 94 1/2" X 47 1/4" approx.

Thickness range: 2-4 mm



COMPOSITION



	Material
Layer 1	Slate
Layer 2	Adhesive
Layer 3	Fiberglass
Layer 4	Base

RECOMMENDATIONS

Recommended adhesive	100217753 POLITECH PREMIUM COMP. A+B	
Recommended joint	100236464 COLORSTUK RAPID MANHATTAN N	
Recommended joint (wet area)	100236464 COLORSTUK RAPID MANHATTAN N	100086920 FILA FOB EXTREME
Recommended adhesive (wet area)	100217753 POLITECH PREMIUM COMP. A+B	

LABORATORY TESTS

Bulk density	1450 Kg/m3	UNE EN 1936:2007*
Water absorption at atmospheric pressure	1.00%	UNE-EN 13755:2008*
Flammability	C-S2, d0	UNE-EN 13501-1:2007+A1:2010*
Frost resistance	93.1 MPa	UNE-EN 12371:2010*
Resistance to thermal shock	T2	UNE -EN 16140:2011*
Flame-spread or surface characteristics	CLASE II	ASTM E 84*
Coefficient of linear thermal expansion	0.5-0.8 MM/M	UNE-EN 10545-8*
Flexural strength	102.2 MPa	UNE-EN 12372:2008*

FEATURES

- Protection that reduces the appearance of the most common domestic bacteria.
- There are considerable color changes between pieces.
- Material from an Asian country.
- Material suitable for use on indoor walls.
- Gloss-free
- Material suitable for use on outdoor walls.
- Material suitable for use on shower walls.
- Material that stands out for having an asymmetrical surface.

PACKING

