

Model: IBIZA WHITE GLOSS**Codes:** 100184180 - L138000811**Group:** G-226**Format:** 3 15/16" X 15 3/4" approx.**Thickness:** 3/8 " approx.

RECOMMENDATIONS

| | |
|---------------------------------|------------------------------|
| Recommended adhesive | 100043280 TIXOCEM PLUS |
| Recommended joint | 100236442 COLORSTUK BLANCO N |
| Recommended joint (wet area) | 100236442 COLORSTUK BLANCO N |
| Recommended adhesive (wet area) | 100043280 TIXOCEM PLUS |

DIMENSIONAL FEATURES

| | | |
|-----------------------------|-----------------------|---------------------|
| Length and width deviation | (±0.5%×±0.5%×±10%) mm | UNE-EN ISO 10545-2* |
| Side straightness deviation | ±0.3% MM | UNE-EN ISO 10545-2* |
| Orthogonality deviation | ±0.5% MM | UNE-EN ISO 10545-2* |
| Surface flatness deviation | (+0.5%/-0.3%) MM | UNE-EN ISO 10545-2* |

FEATURES



Material with surface with the ability to produce reflections.



Material suitable for use on shower walls.



Material suitable for use on indoor walls.

PHYSICAL PROPERTIES

| | | |
|---|----------------|----------------------|
| Water absorption | >10% (BIII) | UNE-EN ISO10545-3* |
| Breaking strength | >600 N | UNE-EN ISO 10545-4* |
| Coefficient of linear thermal expansion | <7 1/(10E6**K) | UNE-EN ISO 10545-8* |
| Resistance to thermal shock | Meets | UNE-EN ISO 10545-9* |
| Crack resistance | Meets | UNE-EN ISO 10545-11* |
| Expansion due to moisture | <0.6 mm/m | UNE-EN ISO 10545-10* |
| Flammability | A1 | UNE-EN 13501-1* |

CHEMICAL PROPERTIES

| | | |
|-------------------------|---------|----------------------|
| Stain resistance | Clase 5 | UNE-EN ISO 10545-14* |
| Resistance to chemicals | GA | UNE-EN ISO 10545-13* |

PACKING

| | |
|--------------|----------------|
| Boxes | 10,76 SQF/CS |
| Pallets | 645,83 SQF/PAL |
| Units | 0,43 SQF/ST |
| Sale unit | M2 |
| Base unit | PIECES |
| Net weight | 33,29 LB/M2 |
| Gross weight | 34,12 LB/M2 |