

Model: LINKFLOOR HOTEL AIR WALNUT

Codes: 100193317 - L167012866


Group: G-228

Format: 48" X 7" approx.

Thickness: 3/16 " approx.



COMPOSITION



	Size	Material	Type of material
Layer 1	0.5	Capa de uso	Capa de uso con protección PU
Layer 2	0.1	vinilo	film decorativo
Layer 3	3.4	PVC + fibra de vidrio	Nucleo de PVC
Layer 4	1	PVC	backing de PVC

CERTIFICATIONS

Floorscore certification	FLOORSCORE
--------------------------	------------

FEATURES



Texture similar to brushed wood



Water-and-moisture resistant floor, suitable for wet areas such as bathrooms and kitchens



5 year warranty for commercial use valid for vinyl materials that have been installed in rooms where they are exposed to normal wear and tear for their recommended End Use Category in accordance with ISO 10582.



Floor capable of dissipating excess electrical charges and distribute them over its entire surface



Installation system where gluing the boards to the floor is not necessary. They are installed on a foam and joined together



15 year warranty for commercial use valid for vinyl materials that have been installed in rooms where they are exposed to normal wear and tear for their recommended End Use Category in accordance with ISO 10582.



Is suitable for installing on water radiant heating



Safety and joint durability are the main features of this easy installation system that guarantees the elimination of gaps between boards throughout the floor's lifetime. The pressure exerted between boards reinforces the union and prevents it from being carried out incorrectly.

DIMENSIONAL FEATURES

Length of face	≤0.5 mm	EN 13329*
Item thickness	≤0.50 mm	EN 13329*
Width of face	≤0.20 mm	EN 13329*
Squareness of the item (q)	≤0.20 mm	EN 13329*
Straightness of face	≤0.30 mm/m	EN 13329*
Flatness of item (f)	fw,Cóncavo≤0.50% fw,Convexo≤1%/fl,Cóncavo≤0.15% fl,Convexo≤0.20%	EN 13329*
Joint between items	≤0.20 mm	EN 13329*
Difference in height among items	≤0.15 mm	EN 13329*
Dimensional variations related to changes in relative moisture	≤0.9 mm	EN 13329*
Punching	No visible changes	EN 433*

LABORATORY TESTS

Commercial area class	33	EN 10582*
Slip resistance (r)	R-10	DIN 51130*
Abrasion resistance	≤0.015 g/1000 ciclos-T	EN 660-1,2*
Resistance to staining	Clase 0	EN 423*
Castor chair effect	No damage %	
Swelling in thickness	±0.2 MM	UNE-EN 13329:2000*
Surface stripping	≥1.00 N/mm2	EN 13329 Anexo D*
Dimensional stability	Max≤0.15%	EN 434:1994*
Formaldehyde emissions	E1	UNE-EN 717-2:1995*
Slip resistance (cls)	Clase 1	EN 12633*
Fire resistance	Bfl-s1	EN 13501*
Evaluation of propensity to accumulation of electrostatic charges	≤2 kV	EN 1815*
Heat resistance	R=0.064 m2 K/W	EN 12664*
Thermal conductivity	12.8 m*K/W	UNE- EN 13329*
Fungus test	Clase 1	ASTM G21*
Uv light fastness	>Grado 6	ISO 105*
Asymmetry/arch effect	≤0.2%	EN 427*
Curvature	≤1.5 mm	EN 434:1994*
Resistance of the click	≥14kg/50mm	
Acoustic insulation	IIC=51dB ; STC=55 dB	ASTM E492 ; ASTM E90*
Dynamic coefficient of friction	Clase DS	ANSI 137.1*
Smoke density (burning)	≤450 Dmc	ASTM E622-15*
Impact resistance	No damage KGF/MM2	
Residual footprint	≤3.8% MM	ASTM F1914*
Private area class	23	EN 10582*

PACKING

Boxes	18,67 SQF/CS	
Pallets	821,33 SQF/PAL	
Units	2,33 SQF/ST	
Sale unit	M2	
Base unit	PIECES	
Net weight	24,08 LB/M2	
Gross weight	24,71 LB/M2	

SPECIAL PIECES

SAP	KEA	Description	Group	Boxes	Pallet	Units	SKU	Basic Unit	Net weight	Gross weight
100244657	L167013141	MAMPER LINKFLOOR HOTEL AIR WALNUT 120X7	G-163	2 ST/CS	200 ST/PAL	11 ST/M2	ST	ST	1 KG/ST	1 KG/ST
100177438	L167012714	PERFIL ADH LINKFLOOR HOTEL AIR WALNUT3,5	G-155	20 ST/CS	1000 ST/PAL	9 ST/M2	ST	ST		
100177482	L167012719	ZOCALO LINKFLOOR HOTEL AIR WALNUT 8X220	G-121	14 ST/CS	560 ST/PAL	5 ST/M2	ST	ST	1 KG/ST	1 KG/ST