

Model: TORTONA 1L WALNUT

Codes: 100199462 - L165003915

Group: G-260

Format: 47 1/4" X 5 23/32" X 7/16" approx.


Thickness: 13/32 " approx.



ADDITIONAL NOTES

This material may have some pieces with sapwood. Due to better usage of the wood, any order of this reference may contain mean percentage tables of between 10% and 15%.

COMPOSITION



	Size	Material	Type of material
Layer 1	0.060-0.070	Varnish	Apresto Mate treatment
Layer 2	3	Hardwood Layer	Quercus spp
Layer 3	6	Intermediate Layer	Wood or HDF slats
Layer 4	2	Contracara	Madera de coníferas














TOLERANCES

Length of face	± 0.1 %	
Width of face	±0.2 MM	
Squareness of the item	±0.2% de la anchura	
Difference in height among items	±0.2 MM	
Curvature	0.1% of length.	

LABORATORY TESTS

Resistance to abrasion	≥500	UNE-EN 13696:2009*
Mass per surface	8.60 KG/M2	EN 14342*
Thermal conductivity	0.18 W/mK W/M**K	UNE-EN 12667:2002*
Heat resistance	0.065 m2K/W M2**K/W	UNE-EN 12667:2002*
Formaldehyde emissions	E1	EN 717*
Moisture content	7.00%	UNE-EN 13183-1/AC:2004*
Flammability	Dfl-s1	EN 13501*
Bulk density	626 Kg/m3	UNE-EN 323:1994*
Slip resistance	Clase 2	UNE-CEN/TS 15676:2008*
Biological durability	Clase 1	UNE EN 335 -1 ; UNE EN 335-2*

FEATURES

-  Safety and joint durability are the main features of this easy installation system that guarantees the elimination of gaps between boards throughout the floor's lifetime. The pressure exerted between boards reinforces the union and prevents it from being carried out incorrectly.
-  Slight smoothing of the wood using a brush to achieve a surface with a slight relief.
-  L'ANTIC COLONIAL's varnishing, in two finishes, APRESTO (gloss) and APRESTO MATE (matte), provides a unique surface quality that satisfies the most demanding requirements. Advantages: It achieves the highest cleanliness because, since the pores are seal...
-  Is suitable for installing on water radiant heating
-  Material with few knots on its surface that can have different sizes depending on the type of wood. These, along with any cracks that may appear, are covered with putty.
-  It is necessary to apply adhesive for installing it.
-  There are consistent color changes between pieces.
-  Material from a North American country.
-  Noble layer
-  Applying a color oil or varnish on the wood surface in order to get different color ranges.
-  Beveled cut on the long sides of the board in order to create a continuity effect
-  Quality product made with selected raw materials, guaranteeing its full residential use for 30 years as provided by L' Antic Colonial.
-  Format where only one board has been used to finish the entire base surface
-  Installation system where gluing the boards to the floor is not necessary. They are installed on a foam and joined together
-  Made with oak wood.
-  Material from a European country.
-  PanEuropean Forest Certification that guarantees to consumers the origin of the products from sustainably managed forests

PACKING

Boxes	16,86 SQF/CS
Pallets	404,55 SQF/PAL
Sale unit	M2
Base unit	ST
Net weight	20,27 LB/M2
Gross weight	21,67 LB/M2

SPECIAL PIECES

SAP	KEA	Description	Group	Boxes	Pallet	Units	SKU	Basic Unit	Net weight	Gross weight
100153884	L165003122	IGUALACION TORTONA WALNUT 4,5X270X1,3	G-161	10 ST/CS	1000 ST/PAL	9 ST/M2	ST	ST	1 KG/ST	1 KG/ST
100176588	L165003670	MAMPERLAN TORTONA 1L WALNUT 120X7X3	G-163	2 ST/CS	200 ST/PAL	11 ST/M2	ST	ST	1 KG/ST	1 KG/ST
100153891	L165003128	TRANSICION TORTONA WALNUT 4X270X1,3	G-161	10 ST/CS	1000 ST/PAL	9 ST/M2	ST	ST	1 KG/ST	1 KG/ST
100153898	L165003125	ZOCALO TORTONA WALNUT 8X220X1,4	G-128	12 ST/CS	600 ST/PAL	5 ST/M2	ST	ST	1 KG/ST	1 KG/ST