

Model: AC4 RESIDENCE 1L ARIZONA

Codes: 100201388 - L167012879


Group: G-200

Format: 7 19/32" X 54 11/32" X 5/16" approx.

Thickness: 5/16 " approx.



COMPOSITION



	Size	Material	Type of material
Layer 1	0.2	Melamine	Aminoplastic thermosetting resins
Layer 2	0.2	Decorative paper	
Layer 3	7.5	HDF	High-density Fiber Board and water-repellent glues
Layer 4		Contracara	Hojas de papel kraft impregnadas con resinas fenólicas

CERTIFICATIONS

Carb certification	CARB: Phase II compliant
--------------------	--------------------------

FEATURES

Imitates the surface of wood

Gloss-free

20 year warranty for domestic use valid for laminate floors that have been installed in rooms where they are exposed to normal wear and tear for their recommended End Use Category in accordance with EN 13329.

Format where only one board has been used to finish the entire base surface

Floor capable of dissipating excess electrical charges and distribute them over its entire surface

23. Intensive residential

AC4 Abrasion-resistance level as per Standard UNE-EN 13329

Beveled cut on all 4 edges of the board for emphasizing size

Installation system where gluing the boards to the floor is not necessary. They are installed on a foam and joined together

5 year warranty for commercial use valid for laminate floors that have been installed in rooms where they are exposed to normal wear and tear for their recommended End Use Category in accordance with EN 13329.

Is suitable for installing on water radiant heating

It is one of the easiest to install and safest systems in the market. We just need to adjust the board to be installed longitudinally to the one already placed, by applying a soft pressure without the need for any type of tool. Both pieces will fit and will be secured thanks to the safety tab. It is just as simple to take apart, which makes for a quick disassembly

32. General commercial

DIMENSIONAL FEATURES

Item thickness	≤0.50 mm	EN 13329*
Length of face	≤0.50 mm	EN 13329*
Width of face	≤0.20 mm	EN 13329*
Squareness of the item (q)	≤0.20 mm	EN 13329*
Straightness of face	≤0.30 mm/m	EN 13329*
Flatness of item (f)	fw,Cóncavo≤0.50% fw,Convexo≤1%/fl,Cóncavo≤0.15% fl,Convexo≤0.20%	EN 13329*
Joint between items	≤0.20 mm	EN 13329*
Difference in height among items	≤0.15 mm	EN 13329*
Dimensional variations related to changes in relative moisture	≤0.90 mm	EN 13329*
Uv light fastness	≥4	EN 438-2,16*
Punching	No visible changes	EN 433*
Surface stripping	≥1.00 N/mm2	EN 13329 Anexo D*

LABORATORY TESTS

Resistance to abrasion	AC4	UNE EN 13329:2000*
Impact resistance	IC2	UNE EN 13329*
Resistance to staining	Grado 5 (G 1 y 2) y Grado 4 (G 3)	EN 438*
Resistance to cigarette burns	4	EN 438*
Furniture leg effect	No damage	EN 424*
Castor chair effect	No damage	EN 425*
Swelling in thickness	≤18%	UNE-EN 13329*
Resistance to microscratching	Class 1	EN 16094*
Formaldehyde emissions	E1	DIN EN 120*
Tensile strength of joints	>1.0 MPA	EN 13329*
Fire resistance	Cfl-s1	EN 13501*
Evaluation of propensity to accumulation of electrostatic charges	≤2 kV	EN 1815*
Heat resistance	R=0.065 m2 K/W	UNE-EN 12667:2002*
Thermal conductivity	0.17 W/mk	DIN 52612*
Swelling in thickness	≤18%	ASTM D 1037*
Slip resistance (dcof)	Clase DS	EN 14041*
Density of the board	840±5 KG/M3	UNE EN 323*

PACKING

Boxes	22,93 SQF/CS	
Pallets	1284,35 SQF/PAL	
Units	2,87 SQF/ST	
Sale unit	M2	
Base unit	PIECES	
Square meters	1 M2	
Net weight	15,89 LB/M2	
Gross weight	16,31 LB/M2	

SPECIAL PIECES

SAP	KEA	Description	Group	Boxes	Pallet	Units	SKU	Basic Unit	Net weight	Gross weight
100202626	L167012884	IGUALACION RESIDENCE ARIZONA 4X270X1	G-155	20 ST/CS	1000 ST/PAL	9 ST/M2	ST	ST		
100202646	L167012889	MAMPERLAN AC4 RESIDENCE 1L ARIZONA 120X7	G-163	2 ST/CS	200 ST/PAL	11 ST/M2	ST	ST	1 KG/ST	1 KG/ST
100202639	L167012894	TRANSICION RESIDENCE ARIZONA 4X270X1	G-155	20 ST/CS	1000 ST/PAL	9 ST/M2	ST	ST		
100202648	L167012899	ZOCALO RESIDENCE ARIZONA 8X220X1,5	G-107	14 ST/CS	560 ST/PAL	5 ST/M2	ST	ST	1 KG/ST	1 KG/ST