

**Model:** TANZANIA ALMOND 25X150(A)

**Codes:** 100202097 - V52500011

**Water absorption:** Bla - Porcelain tiles ( $E \leq 0.1\%$ )

**Thickness:** 13/32 " approx.



### DIMENSIONAL FEATURES

|                             |                   |               |
|-----------------------------|-------------------|---------------|
| Thickness                   | 13/32 " approx.   |               |
| Width                       | 9 13/16 " approx. |               |
| Length                      | 59 1/32 " approx. |               |
| Length and width deviation  | Below 0.15%       | $\leq 0.5\%*$ |
| Side straightness deviation | Below 0.15%       | $\leq 0.5\%*$ |
| Squareness deviation        | Below 0.15%       | $\leq 0.6\%*$ |
| Surface flatness deviation  | Below 0.15%       | $\leq 0.5\%*$ |

\*ASTM C485/C499/C502

### MECHANICAL FEATURES

|                     |                  |               |
|---------------------|------------------|---------------|
| Breaking strength   | 916,47 LBF       | $>292$ LBF*   |
| Modulus of rupture  | 14,33 LBF        | $\geq 8$ LBF* |
| Abrasion resistance | 3 - 600 Rev.     |               |
| Crazing resistance  | Resists 3 cycles |               |

\*ASTM C648

### HYGIENIC FEATURES

|                     |                                                                                                            |                |
|---------------------|------------------------------------------------------------------------------------------------------------|----------------|
| Chemical resistance | Class "A" for swimming pools and cleaning products (resists attack). Minimum Class "B" for acids and bases | CLASE B Min. * |
| Stain resistance    | Class 5. Easy cleaning with water                                                                          | CLASE 3 Min. * |

\*ASTM C650/C1378

### SCOPE OF USE

|                  |                              |  |
|------------------|------------------------------|--|
| Technical code-1 | Use on medium traffic floors |  |
|------------------|------------------------------|--|

### ANTI-SLIP VALUE

|                                 |      |  |
|---------------------------------|------|--|
| Dynamic coefficient of friction | 0.59 |  |
| Slip resistance (ramp)          | R-10 |  |
| Slip resistance (bare feet)     | A    |  |
| 4s                              | 37   |  |

\*ANSI A137.1

### PACKING

|         |                |  |
|---------|----------------|--|
| Boxes   | 16,15 SQF/CS   |  |
| Pallets | 516,66 SQF/PAL |  |
| Units   | 4,04 SQF/ST    |  |

System Certification



Do not use cleaning agents containing hydrofluoric acid.  
It is recommended to fix tiles with a minimum joint of 1,5 mm. Do not fix without joint.  
For big sizes, it is recommended to fix with mortars containing polymeric additives and to use the double gluing technique.  
Mosaic tiles must be grouted.

This document is only commercial and cannot be used as expert opinion, documentary evidence or in any legal or administrative procedure unless authorized by PORCELANOSA S.A.  
A DCOF value of  $> 0.42$  is the new standard for tiles specified for commercial level interior applications expected to be walked upon when wet, in standard A137.1-2012. It replaces the SCOF value of  $> 0.60$  referenced in ADA Guidelines (measurement made as per the ASTM C1028 test method) However, there are many factors that affect the possibility of a slip occurring and then tiles with a DCOF of 0.42 or greater are not necessarily suitable for all projects. The specifier shall determine if tiles are appropriate for specific project conditions, considering by way of example, but not limited to: type of use, traffic, expected contaminants, expected maintenance, expected wear and manufacturer guidelines and recommendations. Tiles with a DCOF inferior to 0.42 shall only be installed when the surface will kept dry when walked upon and proper safety procedures are followed when cleaning the tiles.