

Model: LINKFLOOR EMPIRE LIGHT GREY

Codes: 100203334 - L165003957


Group: G-230

Format: 9" X 70 7/8" approx.

Thickness: 9/32 " approx.



### COMPOSITION



	Size	Material	Type of material
Layer 1	0.5	Wear layer	Use layer with PU protection
Layer 2	0.1	Vinyl	capa decorativa vinícola
Layer 3	0.9	Elastic PVC	Intermediate comfort layer
Layer 4	4.5	WPC	Cuerpo del material compuesto de WPC

### CERTIFICATIONS

Floorscore certification	FLOORSCORE
--------------------------	------------

### ADDITIONAL NOTES

Note	In installations with underfloor heating the temperature must not exceed 27°
------	--

### FEATURES

-  Texture similar to brushed wood
-  Water-and-moisture resistant floor, suitable for wet areas such as bathrooms and kitchens
-  5 year warranty for commercial use valid for vinyl materials that have been installed in rooms where they are exposed to normal wear and tear for their recommended End Use Category in accordance with ISO 10582.
-  Floor capable of dissipating excess electrical charges and distribute them over its entire surface
-  Installation system where gluing the boards to the floor is not necessary. They are installed on a foam and joined together
-  15 year home use warranty valid for vinyl materials that have been installed in rooms where they are exposed to normal wear and tear for their recommended End Use category in accordance with ISO 10582.
-  Is suitable for installing on water radiant heating
-  Safety and joint durability are the main features of this easy installation system that guarantees the elimination of gaps between boards throughout the floor's lifetime. The pressure exerted between boards reinforces the union and prevents it from being carried out incorrectly.



### LABORATORY TESTS

Commercial area class	33	
Slip resistance (r)	R-10	DIN 51130*
Abrasion resistance	≤0.015g/1000 circles	EN 660-1:99*
Furniture leg effect	≤0.015 g/1000 ciclos	EN 424*
Castor chair effect	No damage %	
Swelling in thickness	±0.2 MM	ISO 24336*
Slip resistance (cls)	17 (Clase 1)	UNE-ENV 12633*
Tensile strength of joints	Longitudinal: F0.2=2.35 kN/m; Transversal: F0.2=1.90 kN/m	ISO 24334*
Fire resistance	Bfl-S1	EN13501-1*
Evaluation of propensity to accumulation of electrostatic charges	≤2 kV	EN 1815*
Heat resistance	0.064 M2**K/W	EN 12664*
Fungus test	1	ASTM G21:96*
Residual footprint	Average=0.08 mm ; max=0.092 mm	ISO 24343-1*
Acoustic insulation	IICc=56 dB ; ΔIICc=28 dB ; STC=51 dB	ASTM E2179-08 ; ASTM E989-12*
Dynamic coefficient of friction	Clase DS	ANSI 137.1*
Impact resistance	No damage KGF/MM2	
Private area class	23	

### PACKING

Boxes	17,72 SQF/CS	
Pallets	1133,86 SQF/PAL	
Units	4,43 SQF/ST	
Sale unit	M2	
Base unit	PIECES	
Net weight	17,68 LB/M2	
Gross weight	18,3 LB/M2	

### SPECIAL PIECES

SAP	KEA	Description	Group	Boxes	Pallet	Units	SKU	Basic Unit	Net weight	Gross weight
100241491	L167013089	MAMPER LINKFLOOR EMPIRE LIGHT GREY 120X7	G-163	2 ST/CS	200 ST/PAL	11 ST/M2	ST	ST	1 KG/ST	1 KG/ST
100211800	L167012922	PERFIL ADH LINKFLOOR EMPIRE LIGHTGREY3,5	G-155	20 ST/CS	1000 ST/PAL	9 ST/M2	ST	ST		
100211747	L167012923	ZOCALO LINKFLOOR EMPIRE LIGHT GREY 8X220	G-121	14 ST/CS	560 ST/PAL	5 ST/M2	ST	ST	1 KG/ST	1 KG/ST