

**Model:** NAZARI ASILAH**Codes:** 100213765 - L138001041**Group:** G-231**Format:** 4 17/32" X 4 17/32" X 13/32"-7/16" approx.**Thickness:** 13/32 " approx.

### RECOMMENDATIONS

Recommended adhesive	100043280 TIXOCEM PLUS	
Recommended joint	100236419 COLORSTUK BEIGE N	
Recommended joint (wet area)	100236419 COLORSTUK BEIGE N	
Recommended adhesive (wet area)	100043280 TIXOCEM PLUS	

### DIMENSIONAL FEATURES

Length and width deviation	( $\pm 0.5\% \times \pm 0.5\% \times \pm 10\%$ ) mm	UNE-EN ISO 10545-2*
Side straightness deviation	$\pm 0.3\%$ MM	UNE-EN ISO 10545-2*
Orthogonality deviation	$\pm 0.5\%$ MM	UNE-EN ISO 10545-2*
Surface flatness deviation	( $+0.5\%/-0.3\%$ ) MM	UNE-EN ISO 10545-2*

### FEATURES



Material with surface with the ability to produce reflections.



Material suitable for use on shower walls.



Material suitable for use on indoor walls.

### PHYSICAL PROPERTIES

Water absorption	>10% (BIII)	UNE-EN ISO10545-3*
Breaking strength	>600 N	UNE-EN ISO 10545-4*
Coefficient of linear thermal expansion	<7 1/(10E6**K)	UNE-EN ISO 10545-8*
Resistance to thermal shock	Meets	UNE-EN ISO 10545-9*
Crack resistance	Meets	UNE-EN ISO 10545-11*
Expansion due to moisture	<0.6 mm/m	UNE-EN ISO 10545-10*
Flammability	A1	UNE-EN 13501-1*

### CHEMICAL PROPERTIES

Stain resistance	Clase 5	UNE-EN ISO 10545-14*
Resistance to chemicals	GA/GLA/GHA	UNE-EN ISO 10545-13*

### PACKING

Boxes	4,27 SQF/CS	
Pallets	363 SQF/PAL	
Units	0,14 SQF/ST	
Sale unit	M2	
Base unit	PIECES	
Net weight	34,51 LB/M2	
Gross weight	35,84 LB/M2	