

Model: NAZARI FES**Codes:** 100213766 - L138001051**Group:** G-231**Format:** 4 17/32" X 4 17/32" X 13/32"-7/16" approx.**Thickness:** 13/32 " approx.

RECOMMENDATIONS

Recommended adhesive	100043280 TIXOCEM PLUS	
Recommended joint	100236806 COLORSTUK GRIS N	
Recommended joint (wet area)	100236806 COLORSTUK GRIS N	
Recommended adhesive (wet area)	100043280 TIXOCEM PLUS	

DIMENSIONAL FEATURES

Length and width deviation	(±0.5%x±0.5%x±10%) mm	UNE-EN ISO 10545-2*
Side straightness deviation	±0.3% MM	UNE-EN ISO 10545-2*
Orthogonality deviation	±0.5% MM	UNE-EN ISO 10545-2*
Surface flatness deviation	(+0.5%/-0.3%) MM	UNE-EN ISO 10545-2*

FEATURES



Material with surface with the ability to produce reflections.



Material suitable for use on shower walls.



Material suitable for use on indoor walls.

PHYSICAL PROPERTIES

Water absorption	>10% (BIII)	UNE-EN ISO10545-3*
Breaking strength	>600 N	UNE-EN ISO 10545-4*
Coefficient of linear thermal expansion	<7 1/(10E6**K)	UNE-EN ISO 10545-8*
Resistance to thermal shock	Meets	UNE-EN ISO 10545-9*
Crack resistance	Meets	UNE-EN ISO 10545-11*
Expansion due to moisture	<0.6 mm/m	UNE-EN ISO 10545-10*
Flammability	A1	UNE-EN 13501-1*

CHEMICAL PROPERTIES

Stain resistance	Clase 5	UNE-EN ISO 10545-14*
Resistance to chemicals	GA/GLA/GHA	UNE-EN ISO 10545-13*

PACKING

Boxes	4,27 SQF/CS	
Pallets	363 SQF/PAL	
Units	0,14 SQF/ST	
Sale unit	M2	
Base unit	PIECES	
Net weight	34,67 LB/M2	
Gross weight	36,01 LB/M2	