

**Model:** NAZARI CHAUEN**Codes:** 100213777 - L138001101**Group:** G-231**Format:** 4 17/32" X 4 17/32" X 13/32"-7/16" approx.**Thickness:** 13/32 " approx.

### RECOMMENDATIONS

|                                 |                            |  |
|---------------------------------|----------------------------|--|
| Recommended adhesive            | 100043280 TIXOCEM PLUS     |  |
| Recommended joint               | 100236806 COLORSTUK GRIS N |  |
| Recommended joint (wet area)    | 100236806 COLORSTUK GRIS N |  |
| Recommended adhesive (wet area) | 100043280 TIXOCEM PLUS     |  |

### DIMENSIONAL FEATURES

|                             |                       |                     |
|-----------------------------|-----------------------|---------------------|
| Length and width deviation  | (±0.5%×±0.5%×±10%) mm | UNE-EN ISO 10545-2* |
| Side straightness deviation | ±0.3% MM              | UNE-EN ISO 10545-2* |
| Orthogonality deviation     | ±0.5% MM              | UNE-EN ISO 10545-2* |
| Surface flatness deviation  | (+0.5%/-0.3%) MM      | UNE-EN ISO 10545-2* |

### FEATURES



Material with surface with the ability to produce reflections.



Material suitable for use on indoor walls.



Material suitable for use on shower walls.

### PHYSICAL PROPERTIES

|                                         |                |                      |
|-----------------------------------------|----------------|----------------------|
| Water absorption                        | >10% (BIII)    | UNE-EN ISO10545-3*   |
| Breaking strength                       | >600 N         | UNE-EN ISO 10545-4*  |
| Coefficient of linear thermal expansion | <7 1/(10E6**K) | UNE-EN ISO 10545-8*  |
| Resistance to thermal shock             | Meets          | UNE-EN ISO 10545-9*  |
| Crack resistance                        | Meets          | UNE-EN ISO 10545-11* |
| Expansion due to moisture               | <0.6 mm/m      | UNE-EN ISO 10545-10* |
| Flammability                            | A1             | UNE-EN 13501-1*      |

### CHEMICAL PROPERTIES

|                         |            |                      |
|-------------------------|------------|----------------------|
| Stain resistance        | Clase 5    | UNE-EN ISO 10545-14* |
| Resistance to chemicals | GA/GLA/GHA | UNE-EN ISO 10545-13* |

### PACKING

|              |             |  |
|--------------|-------------|--|
| Boxes        | 4,27 SQF/CS |  |
| Pallets      | 363 SQF/PAL |  |
| Units        | 0,14 SQF/ST |  |
| Sale unit    | M2          |  |
| Base unit    | PIECES      |  |
| Net weight   | 34,51 LB/M2 |  |
| Gross weight | 35,84 LB/M2 |  |